


Parameter	Reportable Range	Resolution	Measurement method
pH (pH units)	6.5 – 8.0	0.001	Potentiometric sensor
pO <sub>2</sub> (mmHg)	10 – 700	0.1	Amperometric sensor
pCO <sub>2</sub> (mmHg)	10 – 150	0.1	Potentiometric sensor
Na (mmol/L)	100 – 180	0.1	Potentiometric sensor
K (mmol/L)	2.0 – 9.0	0.01	Potentiometric sensor
Ca (mmol/L)	0.25 – 2.5	0.01	Potentiometric sensor
CI (mmol/L)	65 – 140	0.1	Potentiometric sensor
Glu (mg/dL or mmol/L)	20 - 700/1.1 - 38.9	1/0.1	Amperometric sensor
Lac (mg/dL or mmol/L)	2.7 - 180.2/0.3 -20	0.1/0.01	Amperometric sensor
Hct (%PCV or Fraction)	10 – 75 /0.10 – 0.75	1%/0.01	Conductance sensor

### Specification

Throughput	Results in 1 minute after sample aspiration				
Sample volume	140µl				
Quality control	3 or 5 levels QC, External electronic simulator				
Display	7-inch color LCD Display, 800*480				
Interface	4 x USB 2.0 host, 1 x RS232, WLAN				
Input device	Touch screen and barcode scanner				
Power supply	100~240VAC, 50/60Hz				
Battery	4200mAh rechargeable lithium-ion battery, 50 samples continuous testing				
Dimensions (W*H*D)	238*153*310 mm				
Weight	3.65 KG				
Operation Environment	10 °C-31 °C; %RH: 25%-80%; 70 -106.6 KPa				









# Portable, lightweight

- Capable to run 50 samples with fully-charged battery
- · Diagnose at the point of care, patient side, out in the field or exam room

# Easy, Quick and Convenient

- Zero maintenanceMinimize hands on time and training requirement
- Auto-sampling
- Report is ready within one minute after sample aspiration

# Accurate and Reliable

- Innovative microchip liquid control technology and micro-sensor multifunction membrane technology
- High sensitivity and accuracy
  Calibrator, Control and Electronic simulator to TRIPLE guarantee the RESULTS!

- Flexible Data Management
   Acquire patients' information via barcode/QR code
- Up to 10,000 patient data storage
- 4 USB ports and LAN/WiFi for data management
  Optional data management software

- Multi-parameter cartridge
  Multi popular time-sensitive parameters come in one cartridge, including ABG, electrolytes and metabolites
  Single-use cartridge avoids contamination
- Room temperature storage with long shelf-life







рН	pCO₂	pO <sub>2</sub>	Na	K	Cl	Ca	Hct	Glu	Lac