Shaker for Microplates

TS200



Description:

TS200 Shaker for Microplates is with technique of direct brushless DC motor and PID intelligent temperature control. It is mainly used for shaking and cultivation in elisa plates (96/384 wells), tissue culture plates(24/48/96 wells).

Application:

- ◆ Maintaining14°C for ligation reactions.
- Maintaining17°C for storing oocytes.
- Storing samples at ice bucket temperatures.
- Storing enzymes or DNA libraries at your work station.
- Transporting samples from the field at exactly the right temperature.
- Heating samples in the field.
- Enzyme reactions and deactivations.
- PCR sample preparation.

Parameters:

Project	Parameters
Temp. control range	RT.+5°C~80°C
Shaking speed	200-1600rpm
Temp. accuracy	≤±0.5°C
Temp. uniformity	≤±0.5°C
Sample capacity	2pcs microplates or culture plates
Power	150W
Dimension(mm)	280×270×140

Features:

- LCD displays system status and parameters.
- ◆ Stable and reliable operation with high quality switch.
- ◆ Easy to operate with one touch knob.
- Setup the time within 0~100 hours, instrument will make alarm voice when completing.
- With power recovery, instrument will continue to run when power recovers from outage.
- 12-month warranty.

Project	Parameters
Timing range	1min ~ 99h59min
Mixing orbit	3mm
Display accuracy	0.1°C
Heating time	≤10min (from RT. to 80°C)
Heating	Heating film
Voltage	AC100V~240V 50/60Hz
Weight(kg)	7.0